



**VMC-850**



**VMC-1060**



	VMC-650	VMC-855	VMC-1060	VMC-1260	VMC-1370	VMC-1580	VMC-1690
X Axis Travel (mm)	600	850	1000	1200	1300	1500	1600
Y Axis Travel (mm)	450	550	550	600	700	800	900
Z Axis Travel (mm)	500	500	550	600	650	700	800
Distance from spindle to table (mm)	100-600	150-700	180-700	180-780	180-800	170-800	170-840
Spindle center to column surface (mm)	475	550	550	600	780	800	950
Table Size (mm)	750x450	1050x500	1000x500	1400x600	1400x710	1700x800	1800x900
Max. table load (kg)	600	800	1000	1200	1400	1600	1700
T slot width x no. (mm)	18x5	18x5	18x5	18x5	18x5	22x5	22x5
Spindle mount	BT40	BT40	BT40	BT40	BT50	BT50	BT50
Max. Spindle speed (RPM)	8000	8000	8000	8000	8000	6000	6000
Spindle Motor (kw)	7.5	7.5	11	11	15/18.5	15/18.5	18.5
XYZ servo motors (kw) (3 axis motor power)	1.5x1.5x1.5	2x2x2	2x2x2	2x2x2	3.5x3.5x3.5	4.5x4.5x3.5	4.5x7x4.5
Feed Rate (mm/min)	15000/15000/ 12000	15000/15000/ 12000	15000/15000/ 12000	15000/15000/ 12000	15000/15000/ 12000	15000/15000/ 12000	12000/12000/ 12000
Work Feed (mm/min)	1-10000	1-10000	1-10000	1-10000	1-10000	1-10000	1-10000
Positioning Accuracy (mm)	±0.005	±0.005	±0.005	±0.005	±0.005	±0.005	±0.005
Repeatability (mm)	±0.003	±0.003	±0.003	±0.003	±0.003	±0.003	±0.003
Air Pressure (kg/cm <sup>2</sup> )	≥6	≥6	≥6	≥6	≥6	≥6	≥6
Power (KVA)	15	18	20	30	30	50	50
Machine Weight (kg)	4500	5500	7800	10000	11000	14000	14500



Brands



**JINPU**

**SAN**

*Jian Ya*

**Milodon**

**Master**

1732 Aviation Blvd #317  
Redondo Beach, CA 90278  
main (310) 937-4253  
fax (310) 943-6594  
Info@Jinpu-USA.com

<http://www.jinpu-usa.com/cncmills.html>

Imported by Good News Industrial LLC



All Rights Reserved